



8" Fire Alarm Bell Weatherproof GST-JL

Description

Fire alarm bell has a simple structure and red coated steel casing, with novel pattern and easy installation. It is applicable to the fire alarm equipment of factory, workshop, hotel as well as large and medium sized buildings. Under nominal voltage, the alarm sounds clearly and continuously.

Technical Specifications

- Protection Rating: IP65
- Operating voltage: 24Vdc
- Operating Current: 0.060A
- Operating temperature: -10°C to +50°C
- Relative humidity: 95%
- Sound Output: 100dB @ 1metre
- Application: Outdoor
- Material and colour: Stainless Steel; RED
- Built-in High performance gasket on the back box
- Wiring: 1 pair polarized
- Dimensions: Diameter 6 inches

Sounder Installation

The sounder beacon should be installed in compliance with all local codes or NFPA 72 National Fire Alarm Code, NFPA 70 National Electrical Code, BS5389 and EN54. It is install onto a standard one gang electrical box with a mounting hole that has 6.5cm spacing.


Wiring and Connection

The red and black cable is for 24VDC power supply, note the polarity Red is positive and Black is negative. The cable must be fire rated type and the size depends on the wiring distance. Minimum size gauge is 1.00mm sq.

Selection of compatible Control Panels

Compatible with all GST Conventional panel and GST Intelligent Fire Alarm Panels using sounder output and Intelligent Sounder Driver Module

Ordering Information



Part Number: GST-JL
Description: 8" Fire Alarm Bell Weatherproof
Weight / Kg.: 0.60
Pack Qty. per Box: 25