



# Handheld Programmer

P-9910B

## Description

The P-9910B GST protocol programming tool, capable of reading and writing address codes, displaying model number, year of manufacture and batch number, plus display and adjust analogue sensitivity.

Enable to adjust alarm threshold, N/C or N/O and switch on or off the rate of rise of dual heat detector.

## Features and Benefits

- Portable programming tool for addressing and testing of intelligent devices
- Digital programming
- Programs all loop devices (1-242 addresses per loop)
- Non-polarized 2 wire intelligent programmer
- Interrogates devices for conditions
- Reprogram facility enables adjustment to alarm sensitivity of detectors
- Adjust inputs modules to accept N/C or N/O contacts
- Low power consumption with sleep and auto off mode.
- Battery low indication
- Display type: Four-bit LCD
- Easy operation Hand held engineering tool.

## Technical Specifications

- Test Certificate : CE EMC AE50121021
- Single point programming and interrogation of GST detectors and protocol
- Power supply: one 9V battery
- Working current:  $\leq 8\text{mA}$
- Standby current:  $\leq 50\mu\text{A}$
- Operating environment:
- Temperature:  $-20\text{C}+70$
- Relative humidity:  $\leq 95\% 40\pm 2\text{C}$
- Physical dimensions: 164mmx64mmx24mm

## Selection of compatible Control Panels

Compatible with all GST Intelligent fire alarm panel.

## Ordering Information



**Part Number:** P-9910B  
**Description:** Handheld Programmer  
**Pack Qty. per Box:** 1